



HEAVY DUTY SLUGGING / STRIKING WRENCHES

Striking Wrenches are designed to be Struck by a hammer on the anvil area, in order to loosen frozen fasteners or to set and tighten fasteners. Anvils are proportional to wrench opening size. Specially selected alloy steel & the best suited heat treatment provides, maximum durability for long life and to withstand the severe working conditions.

STRAIGHT RING TYPE

Specially Designed for most rugged industrial application. Straight Handle design resists springing while allowing the fastener to turn easier.



Wrench Size (A/F)						
METRIC SIZE		SAE SIZE		Head Dia.	Head Thk.	Length (Mm)
Part No.	Size	Part No.	Size			
TSM -19	19	TS-25	3/4"	54	18	175
TSM -22	22	TS-28	7/8"	54	18	175
TSM -24	24	TS-29	15/16"	54	18	175
TSM -27	27	TS-31	1.1/16"	54	18	175
TSM -29	29	TS-32	1.1/8"	54	18	175
TSM -30	30	TS-33	1.3/16"	68	22	210
TSM -32	32	TS-34	1.1/4"	68	22	210
TSM -33	33	TS-35	1.5/16"	68	22	210
TSM -35	35	TS-36	1.3/8"	68	22	210
TSM -36	36	TS-37	1.7/16"	68	22	210
TSM -38	38	TS-38	1.1/2"	68	22	210
TSM -41	41	TS-39	1.5/8"	80	28	245
TSM -43	43	TS-40	1.11/16"	80	28	245
TSM -44	44	TS-41	1.3/4"	80	28	245
TSM -46	46	TS-42	1.13/16"	80	28	245
TSM -47	47	TS-43	1.7/8"	80	28	245
TSM -50	50	TS-45	2"	80	28	245
TSM -52	52	TS-46	2.1/16"	102	35	285
TSM -55	55	TS-47	2.3/16"	102	35	285
TSM -57	57	TS-48	2.1/4"	102	35	285
TSM -60	60	TS-50	2.3/8"	102	35	285
TSM -62	62	TS-51	2.7/16"	102	35	285
TSM -63	63	TS-52	2.1/2"	102	35	285
TSM -65	65	TS-53	2.9/16"	102	35	285
TSM -67	67	TS-54	2.5/8"	122	40	322
TSM -70	70	TS-56	2.3/4"	122	40	322
TSM -71	71	TS-57	2.13/16"	122	40	322
TSM -75	75	TS-59	2.15/16"	122	40	322
TSM -76	76	TS-60	3"	122	40	322
TSM -80	80	TS-61	3.1/8"	122	40	322
TSM -85	85	TS-63	3.1/8"	130	40	340
TSM -90	90	TS-64	3.5/8"	136	45	350
TSM -95	95	TS-65	3.3/4"	140	45	375
-	-	TS-66	3.7/8"	158	50	415
TSM -100	100	TS-67	4"	158	50	415
TSM -105	105	TS-68	4.1/8"	164	50	450
TSM -110	110	TS-69	4.1/4"	170	55	450
TSM -115	115	TS-70	4.1/2"	175	55	465
TSM -120	120	TS-72	4.3/4"	190	60	490

Wrench Size (A/F)						
METRIC SIZE		SAE SIZE		Head Dia.	Head Thk.	Length (Mm)
Part No.	Size	Part No.	Size			
TSM -125	125	TS-73	4.7/8"	200	60	510
TSM -130	130	TS-74	5"	210	65	515
TSM -135	135	TS-75	5.3/8"	222	65	540
TSM -140	140	TS-76	5.1/2"	230	70	550
TSM -145	145	TS-78	5.3/4"	230	70	565
TSM -150	150	TS-80	6"	230	70	565
TSM -155	155	TS-81	6.1/8"	230	70	565
TSM -160	160	TS-82	6.1/4"	270	70	635
TSM -165	165	TS-84	6.1/2"	270	70	635
TSM -170	170	TS-86	6.3/4"	270	70	635
TSM -175	175	TS-87	6.7/8"	270	70	635
TSM -180	180	TS-89	7.1/8"	270	70	635
TSM -185	185	TS-90	7.1/4"	295	75	680
TSM -190	190	TS-92	7.1/2"	295	75	680
TSM -195	195	TS-93	7.5/8"	295	75	680
TSM -200	200	TS-95	7.7/8"	295	75	680
TSM -205	205	TS-97	8.1/8"	295	75	680
TSM -210	210	TS-98	8.1/4"	325	80	725
TSM -215	215	TS-100	8.1/2"	325	80	725
TSM -220	220	TS-101	8.5/8"	325	80	725
TSM -225	225	TS-103	8.7/8"	325	80	725
TSM -230	230	TS-105	9.1/8"	325	80	725

SQUARE DRIVE TYPE



Model No.	Sq. Drive	D mm	L mm
TSW-75	3/4"	62	210
TSW-100	1"	76	290
TSW-150	1.1/2"	116	380

