



# HYDRAULIC JACK POWER PACK

## Hydraulic Hand Pumps

Max. Working Pressure 700 bar

### Features

- Heavy duty construction with hardened ground and plated piston.
- Replaceable cartridge valves.
- Durable polyurethane plunger seal.
- Collapsible handle - faster stroke at low pressure.


Pump Stage	Single	Single	Two
Oil Tank Capacity (Ltrs.)	1.8	2.2	5
Model	TMP 2	TMP 3	TMP 5
Pressure (kg/cm <sup>2</sup> )			
1 <sup>st</sup> stage	-	-	30
2 <sup>nd</sup> stage	700	700	700
Flow / Stroke (cc)			
1 <sup>st</sup> stage	-	-	49
2 <sup>nd</sup> stage	2.8	2.8	2.8
Handle Effort (Kg)	40	40	40

Pump Stage	Two	Two	Two
Oil Tank Capacity (Ltrs.)	8	5	8
Model	TMP 8	TMP 6	TMP 9
Pressure (kg/cm <sup>2</sup> )			
1 <sup>st</sup> stage	30	30	30
2 <sup>nd</sup> stage	700	700	700
Flow / Stroke (cc)			
1 <sup>st</sup> stage	49	49	49
2 <sup>nd</sup> stage	2.8	2.8	2.8
Handle Effort (Kg)	40	40	40

Note: TMP6 & TMP9 are installed with Directional Control Valve.



Single Stage Hand Pump



Two Stage Hand Pump With DCV

## Power Pack

### 1. Model No. THP-SS2

- Motor Capacity: 2HP Single phase
- Oil Tank Capacity: 20 litre
- Flow rate: Above 150 bar = 1.0 l/min
- Max. Pressure: 700 bar

### 2. Model No. THP-DS3

- Motor Capacity: 3HP Single phase
- Oil Tank Capacity: 40 litre
- Flow rate: Upto 150 bar = 7.3 l/min  
Above 150 bar = 1.5 l/min
- Max. Pressure: 700 bar


### 3. Model No. THP-DT5

- Motor Capacity: 5HP Three phase
- Oil Tank Capacity: 50 litre
- Flow rate: Upto 150 bar = 12.3 l/min  
Above 150 bar = 2.6 l/min
- Max. Pressure: 700 bar


### 4. Model No. THP-DT7.5

- Motor Capacity: 7.5HP Single phase
- Oil Tank Capacity: 80 litre
- Flow rate: Upto 150 bar = 17.3 l/min  
Above 150 bar = 3.7 l/min
- Max. Pressure: 700 bar

**Note:** We also provide customized Power Pack as per required specifications.



Three Phase Double Pump Power Pack



Single Phase Single Pump Power Pack

## ACCESSORIES FOR JACKS

### Hoses

- 3/8" female-male end length- 2m, 3m, 4m, 6m, 10m

### Coupler with cap

- 3/8" female end with cap
- 3/8" male end with cap

### Manifold Blocks

Model No.	Description
TM12H	1 inlet, 2 outlets Hex type
TM12N	1 inlet, 2 outlets Normal type
TM14N	1 inlet, 4 outlets Normal type
TM12NS	1 inlet, 2 outlets with Shut off valve
TM14NS	1 inlet, 4 outlets with Shut off valve
TM16NS	1 inlet, 6 outlets with Shut off valve
TM24NS	2 inlet, 4 outlets with Shut off valve



Please observe safety advices